

ENERGY KNOWLEDGE FUTURE



EKF is an international electrical solutions brand, specializing in power distribution equipment and automation systems for industrial, commercial, and residential applications, as well as civil infrastructure projects. The company's portfolio extends beyond hardware to include advanced software solutions, featuring the EKF Connect Home smart home ecosystem and the EKF Connect Industry cloud-based IIoT platform.



19 000+ SKUs



20+ countries of operation



Extensive distribution network



Rapid delivery



20+ years of experience




In-house Research & Development



Engineering services and project support department





QUALITY ASSURANCE, RESEARCH AND DEVELOPMENT

ISO 9001:2015 compliant world-class manufacturing facilities, validated by TÜV in 2020











Quality control by an in-house testing lab. Products certified by DEKRA, TÜV and other globally accredited certification companies










CONTENT

HAND TOOLS	5
SCREWDRIVERS	6
INSULATED SCREWDRIVERS	7
PLIERS	9
INSULATED PLIERS	10
TOOL SETS	11
UTILITY KNIVES	12
CABLE AND WIRE CUTTERS	13
WIRE STRIPPERS	20
WIRE CRIMPERS	35
MEASURING DEVICES	41
TAPE MEASURES	42
LASER DISTANCE METERS	43
MULTIMETERS	44
EARTH RESISTANCE TESTER	49
CLAMP METERS	50
PYROMETER	53
LAN & TELECOM TOOLS	54
ABC INSTALLATION TOOLS AND ACCESSORIES	57
DIRECT FASTENING TECHNOLOGY	60
CONSUMABLES	67
CORE DRILL BITS	68
DRILLING TEMPLATES	72
DIAMOND CUTTING DISCS	73
DRILL BITS	74
STEP DRILL BITS	76
CHISELS	77
PERSONAL PROTECTIVE EQUIPMENT	78
TOOL BAGS, BACKPACKS, TOOL BELTS	81





	Picture	Name	Tip	Shank size	Item code
		Slotted screwdriver SL3,5×75 mm MASTER EKF		3,5×75×0,6 mm	sl-3.5-75-mas
		Slotted screwdriver SL4×100 mm MASTER EKF	SL (Slotted/Flat)	4×100×0,8 mm	sl-4-100-mas
MASTER		Slotted screwdriver SL5,5×125 mm MASTER EKF	Θ	5,5×125×1,0 mm	sl-5.5-125-mas
		Slotted screwdriver SL6,5×38 mm MASTER EKF		6,5×38×1,2 mm	sl-6.5-38-mas
		Phillips screwdriver PH0×75 mm MASTER EKF	Ph (Phillips)	PH0×75 mm	ph-0-75-mas
М		Phillips screwdriver PH1×100 mm MASTER EKF		PH1×100 mm	ph-1-100-mas
		Phillips screwdriver PH2×100 mm MASTER EKF		PH2×100 mm	ph-2-100-mas
	Č)	Phillips screwdriver PH3×150 mm MASTER EKF		PH3×150 mm	ph-3-150-mas
		Pozidriv screwdriver PZ1×100 mm MASTER EKF	Pz (Pozidriv)	PZ1×100 mm	pz-1-100-mas
		Pozidriv screwdriver PZ2×100 mm MASTER EKF	₩	PZ2×100 mm	pz-2-100-mas



	Picture	Name	Tip	Shank size	Item code
		Insulated Phillips screwdriver PH1×80 mm VDE 1000 V PROFESSIONAL EKF	Ph (Phillips)	PH1×80 mm	ph-1-80-pro-in
		Insulated Phillips screwdriver PH2×100 mm VDE 1000 V PROFESSIONAL EKF	•	PH2×100 mm	ph-2-100-pro-in
		Insulated combination Phillips/Flat screwdriver PH-FL1×80 mm 1000 V PROFESSIONAL EKF	Ph-Fl (Phillips - Flat)	PH-FL1×80 mm	ph-fl-1-80-pro-in
PROFESSIONAL	PH-FL2×100 mm 1000 V VDE PROFESSIONA	Insulated combination Phillips/Flat screwdriver PH-FL2×100 mm 1000 V VDE PROFESSIONAL EKF	•	PH-FL2×100 mm	ph-fl-2-100-pro-in
SSIC	Made in Germany	Insulated combination Pozidriv/Flat screwdriver PZ-FL1×80 mm 1000 V VDE PROFESSIONAL EKF	Pz-Fl (Pozidriv - Flat)	PZ-FL1×80 mm	pz-fl-1-80-pro-in
ROF		Insulated Pozidriv/Flat screwdriver PZ-FL2×100 mm 1000 V VDE PROFESSIONAL EKF	` ₩ ΄	PZ-FL2×100 mm	pz-fl-2-100-pro-in
Δ	1000 V	Insulated Slotted screwdriver SL2,5×0,4 mm 1000 V VDE PROFESSIONAL EKF		2,5×0,4×2,5 mm	sl-2.5-0.4-pro-in
		Insulated Slotted screwdriver SL3,5×0,6 mm 1000 V VDE PROFESSIONAL EKF	SL (Slotted/Flat)	3,5×0,6×3,5 mm	sl-3.5-0.6-pro-in
		Insulated Slotted screwdriver SL4×0,8 mm 1000 V VDE PROFESSIONAL EKF		4×0,8×4 mm	sl-4-0.8-pro-in
		Insulated Slotted screwdriver SL5,5×1 mm 1000 V VDE PROFESSIONAL EKF		5,5×1×5,5 mm	sl-5.5-1-pro-in

6 ekfgroup.com ekfgroup.com 7



VOLTAGE TESTERS

	Picture	Characteristics	Voltage tester OI-1 MASTER EKF
		AC voltage presence detection	70-600 V
监		DC voltage presence detection	250 V
MAST		DC circuit continuity and polarity test	1,5-6 V
		De-energized circuit continuity check	Yes
		Item code	ST-10

	Picture	Characteristics	Voltage tester OI-2e MASTER EKF
	CC TESTER	AC voltage presence detection	70-1000 V
딾		DC voltage presence detection	250 V
MASTER		DC circuit continuity and polarity test	1,2-36 V
		De-energized circuit continuity check	Yes
		Item code	ST-20e









	Picture	Name	Length, mm	Item code
		Combination pliers 160 mm MASTER EKF	160	pas-160-mas
		Combination pliers 180 mm MASTER EKF	180	pas-180-mas
		Combination pliers 200 mm MASTER EKF	200	pas-200-mas
	*	Long nose pliers 160 mm MASTER EKF	160	dg-160-mas
	*	Curved long nose pliers 160 mm MASTER EKF	160	dgi-160-mas
MASTER	1	Cable cutters NK-12 MASTER EKF	170	nk-12-mas
Σ		Cable cutters NK-16 MASTER EKF	240	nk-16-mas
	*	Diagonal cutters 160 mm MASTER EKF	160	bo-160-mas
	*	Reinforced diagonal cutters 180 mm MASTER EKF	180	sbo-180-mas
	*	Round nose pliers 160 mm MASTER EKF	160	kg-160-mas



INSULATED PLIERS



	u		

	Picture Name		Length, mm	Item code
		Insulated combination pliers 160 mm 1000 V EXPERT EKF	160	pas-160-exp-in
		Insulated combination pliers 180 mm 1000 V EXPERT EKF	180	pas-180-exp-in
	Insulated long nose pliers 160 mm 1000 N	Insulated long nose pliers 160 mm 1000 V EXPERT EKF	160	dg-160-exp-in
EXPERT	H	Insulated curved long nose pliers 160 mm 1000 V EXPERT EKF	160	dgi-160-exp-in
Ë		Insulated cable cutters NKi-12u 1000 V EXPERT EKF	170	nk-12y-exp-in
	11	Insulated cable cutters NKi-16u 1000 V EXPERT EKF	240	nk-16y-exp-in
	M	Insulated diagonal cutters 160 mm 1000 V EXPERT EKF	160	bo-160-exp-in
	M	Insulated reinforced diagonal cutters 180 mm 1000 V EXPERT EKF	180	sbo-180-exp-in

	Picture	Name	Description	Item code
EXPERT	€E A C	Insulated tool set NII-01 EXPERT EKF	Screwdriver SL2,5×80 mm 1000 V EXPERT EKF - 1 pc. Screwdriver SL4×100 mm 1000 V EXPERT EKF - 1 pc. Screwdriver SL5,5×125 mm 1000 V EXPERT EKF - 1 pc. Screwdriver PH1×80 mm 1000 V EXPERT EKF - 1 pc. Screwdriver PH2×100 mm 1000 V EXPERT EKF - 1 pc. Combination pliers 180 mm 1000 V EXPERT EKF - 1 pc. Reinforced diagonal cutters 180 mm 1000 V EXPERT EKF - 1 pc. Long nose pliers 160 mm 1000 V EXPERT EKF - 1 pc. Voltage tester OI-1 EKF - 1 pc. Soft case - 1 pc.	ndi-O1

Picture	Name	Description	Item code
Nade in Germany	Insulated screwdriver set NIO-10 PROFESSIONAL EKF	Insulated slotted screwdriver SL3,5×0,6 mm 1000V VDE PROFESSIONAL EKF - 1 pc. Insulated slotted screwdriver SL4×0,8 mm 1000V VDE PROFESSIONAL EKF - 1 pc. Insulated slotted screwdriver SL5,5×1 mm 1000V VDE PROFESSIONAL EKF - 1 pc. Insulated Phillips screwdriver PH1×80 mm 1000V VDE PROFESSIONAL EKF - 1 pc. Insulated Phillips screwdriver PH2×100 mm 1000V VDE PROFESSIONAL EKF - 1 pc. Voltage tester Ol-1 EKF - 1 pc.	ndo-10







UTILITY

KNIVES









18 mm WIDE SNAP-OFF BLADES TIGHTER CLEARANCE BETWEEN THE BLADE AND THE BLADE HOLDER

1,2 mm THICK METAL BLADE HOLDER AUTO LOCK- QUICK, AUTOMATIC DOUBLE-SIDED BLADE LOCK

	Picture	Name	Blade width, mm	Blade thickness, mm	Item code
EXPERT		Heavy duty snap-off utility knife 18 mm NCM-50 EXPERT EKF		0,5	ncm-50-exp
PROFESSIONAL		Heavy duty snap-off utility knife 18 mm NCM-50 PROFESSIONAL EKF	18	0,7	ncm-80-pro

SPARE SNAP-OFF BLADES

	Picture	Name	Blade thickness, mm	Blade width, mm	Steel grade	Item code
EXPERT		Snap-off blades 18 mm CM-30 EXPERT EKF	0,5		SK4 high-carbon	cm-s30
PROFESSIONAL		Snap-off blades 18 mm CM-60 PROFESSIONAL EKF	0,7	18	SK4 high-carbon tool steel	cm-s60

RATCHET CABLE CUTTERS

Model	Unarmored cable	Steel tape armored cable	Steel wire armored cable	Aluminium conductor steel-reinforced cable	Steel rope 1×7	Steel rope 1×19	Low carbon steel rebar and fittings, chains
						••••	• •
Ratchet cable cutter NC-70BC EXPERT EKF	75	75	70	-	-	-	-
Ratchet cable cutter NC-100BCR EXPERT EKF	110	110	-	-	-	-	-
Ratchet cable cutter NC-30C EXPERT EKF	-	-	10	35	10	-	-
Ratchet cable cutter NC-50BAC EXPERT EKF	-	-	16	50	12	16	16
Ratchet cable cutter NC-45BC EXPERT EKF	45	45	-	-	-	-	-

12 ekfgroup.com ekfgroup.com 13



CABLE AND WIRE CUTTERS

CABLE AND WIRE CUTTERS

RE CUTTERS E	EKF
--------------	-----

Picture	Name	Ratchet cable cutter NC-45BC EXPERT EKF		Picture	Name	
	Description	Ratchet cable cutter NC-45BC is designed for cutting stranded copper and aluminium cables with a maximum diameter of 45 mm. Total cable cross-section: 400 mm²			Description	Ratchet cable cutter NO aluminium cable, steel ross-section: Al cable cross-section: Mild steel rebar diamete: Steel chain diameter: 12 Great for cutting ABC.
A	Features	 Return spring for easy one hand operation Unlock latch to open up the cutter at any time Smaller ratchet gear teeth to decrease cutting effort Fold down handle lock to reduce storage dimensions 	ЕХРЕКТ		Features	Cuts steel core aluminiu Unlock latch to open up Smaller ratchet gear tee Screw connection of the Blades can be re-sharpe
	Weight, g	900			Weight, g	
	Length, mm	283			Length, mm	
	Delivery scope	Ratchet cable cutter; technical manual, storage and carrying bag			Delivery scope	Rat
	ltem code	nc-45			Item code	

Picture	Name	Ratchet cable cutter NC-30C EXPERT EKF		
	Description	Ratchet cable cutter NC-30C with replaceable blades is designed for cutting stranded copper and aluminium cables, including armored aluminium core cable and low-alloy steel rebar. Steel core aluminium cable diameter: 35 mm. Al cable cross-section: 630 mm². Steel rope diameter: 30 mm. Low-alloy steel rebar diameter: 14 mm. Steel chain diameter: 10 mm. Great for cutting ABC.		
	Features	Replaceable blades Unlock latch to open up the cutter at any time Smaller ratchet gear teeth to decrease cutting effort Screw connection of the blades so that they can be retightened Blades can be re-sharpened		
	Weight, g	3650		
	Length, mm	400		
	Delivery scope	Ratchet cable cutter; technical manual, storage and carrying bag		
	Item code	nc-30		

Picture	Name	Ratchet cable cutter NC-50BAC EXPERT EKF
	Description	Ratchet cable cutter NC-50BAC is designed to cut stranded copper, armored aluminium cable, steel core aluminium cable, steel repar. Steel core aluminium cable diameter: 50 mm (cross-section: 1962 mm²). Cu cable cross-section: 400 mm². Al cable cross-section: 400 mm². Mild steel rebar diameter: 16 mm. Steel chain diameter: 12 mm. Great for cutting ABC.
	Features	Cuts steel core aluminium cable with cross-section of up to 1440 mm² Unlock latch to open up the cutter at any time Smaller ratchet gear teeth to decrease cutting effort Screw connection of the blades so that they can be retightened Blades can be re-sharpened
	Weight, g	3300
	Length, mm	390
	Delivery scope	Ratchet cable cutter; technical manual, storage and carrying bag
	Item code	nc-50
	Picture Picture	Peatures Weight, g Length, mm Delivery scope











CABLE AND WIRE CUTTERS



	Picture	Name	Ratchet cable cutter NC-70BC EXPERT EKF
		Description	Ratchet cable cutter NC-70BC is designed for cutting stranded copper and aluminium cables, including reinforced armor cables and telephone cables with up to 3600 wire pairs. Cable diameter: 70 mm. Cu cable cross-section: 3×120 mm². Al cable cross-section: 3×150 mm².
EXPERT		Features	Unlock latch to open up the cutter at any time Highly reliable twist-and-lock telescoping handles for easier use Refined ratchet tooth shape for improved durability
		Weight, g	3700
		Length, mm Delivery scope	580
			Ratchet cable cutter; technical manual, storage and carrying bag
		Item code	nc-70

Homic Co





	Picture	Name	Ratchet cable cutter NC-100BCR EXPERT EKF
ЕХРЕКТ		Description	Ratchet cable cutter NC-100BCR is designed for cutting stranded copper and armored copper and aluminium cables. Cable diameter: 100 mm. Cu wire cross-section: 3×300 mm². Al wire cross section: 3×300 mm².
		Features	Unlock latch to open up the cutter at any time Highly reliable twist-and-lock telescoping handles for easier use Refined ratchet tooth shape for improved durability Combination cut/chop blade profile enables even cuts, without pulling and straining the wires
		Weight, g	6650
		Length, mm	510
		Delivery scope	Ratchet cable cutter; technical manual, storage and carrying bag
		Item code	nc-100








17



SPARE PARTS

EKF



EXPERT	المناف	Delivery scope	Moving blade Fixed blade Ratchet with needle bearings Ratchet pawl Pawl spring Ratchet spring Axial screw Axial screw nut Return spring Pin	
		Compatible models	nc-70	
		Item code	slnc-70	

Name

		Picture	Name	Repair kit for ratchet cable cutter NC-100BCR EXPERT EK	F
	EXPERT		Delivery scope	Moving blade Fixed blade Ratchet with needle bearings Axial screw Axial screw nut Multiplier gear Pin	
			Compatible models	nc-100	
			Item code	slnc-100	





ELECTRICIAN'S SCISSORS















TEXTURED HANDLES FOR IMPROVED GRIP

BUILT-IN CRIMPER FOR E AND TE-2 FERRULES

HIGH-QUALITY SOLINGEN STEEL BLADES







TWO-PART HANDLES

HIGH-STRENGTH REINFORCED
POLYAMIDE HANDLES

TRANSVERSE INSULATION STRIPPING

	Picture	Name	Electrician's scissors WS-35 PROFESSIONAL EKF
PROFESSIONAL		Features	Cuts stranded copper cables with cross-section up to 50 mm² as well as plastic and aluminium Not intended for cutting steel Cable stripping blade section Crimps 0,5-4 mm² non-insulated cord end terminals E and TE-2 Plastic clip-on carry case included
		Weight, g	90
	A	Length, mm	150
		Item code	ws-35

















WIRE STRIPPING

BLADE CLAMPING ADJUSTMENT MECHANISM

CRIMPING
OF INSULATED AND
NON-INSULATED CORD
END FERRULES





ADJUSTABLE STRIP STOP

REPLACEABLE CUTTER BLADE


	Picture	Name	Multifunctional automatic stripper WS-04 MASTER EKF
MASTER		Description	Multifunctional automatic stripper is designed for stripping and cutting wires with the cross-section of 0,2-6 mm² and crimping wire cord end ferrules
		Features	 Insulation stripping: 0,2-6 mm² Blade clamping adjustment mechanism Adjustable strip stop Replaceable cutter blade Crimps insulated and non-insulated cord end ferrules
	4 1	Cross-section, mm²	0,2-6,0
		Item code	ws-04

WIRE STRIPPERS



ı	Picture	Name	Multifunctional hand stripper WS-01 MASTER EKF	
		Description	Multifunctional hand stripper is designed for stripping and cutting wires with the cross-section of 0,5-6 mm² and crimping wire cord end ferrules	
		Features	Side cutter for snipping wires in hard to reach places Concealed return spring mechanism. Easy to operate one-handed Strips 0,5-6 mm² wires Crimps insulated and non-insulated cord end ferrules Handle lock for easy storage and carry	
H		Cross-section, mm²	0,5-6,0	
		Item code	ws-01	
ı	Picture	Name	Multifunctional semi-automatic stripper WS-03 MASTER EKF	
		Description	Multifunctional semi-automatic stripper is designed for stripping and cutting wires with the cross-section of 0,5-6 mm² and crimping wire cord end ferrules	
		Features	Insulation stripping: 0,5-6 mm² Built-in stripping stop Blade clamping adjustment mechanism Concealed return spring mechanism. Easy to operate one-handed Replaceable cutter blade Crimps insulated and non-insulated cord end ferrules	
		Cross-section, mm²	0,5-6,0	
•				





21 20 ekfgroup.com ekfgroup.com



AUTOMATIC WIRE STRIPPER WS-11 PROFESSIONAL EKF





























СК	P	
----	---	--







WIRE STRIPPERS

EKF

AUTOMATIC WIRE STRIPPER WS-14 PROFESSIONAL EKF





















5-STEP ADJUSTABLE BLADE CLAMPING
REGULATOR +()-

Picture	Name	Automatic wire stripper WS-14 PROFESSIONAL EKF
(Fere	Description	Made in Germany and featuring a pass-through construction the Automatic wire stripper WS-14 is perfect for stripping outer sheath from 0,75-4 mm² flat cables as well as insulation from 0,5-16 mm² individual wires. Thanks to its design, WS-14 automatically adjusts to the size and type of wire. Easy to maneuver in tight and cramped spaces. Built-in cutter for wires up to 3 mm in diameter. Replaceable Solingen steel blades extend the life of the tool
	Cross-section, mm ²	0,75-4,0
	Item code	ws-14
	Wire type	





MULTIFUNCTIONAL HAND STRIPPER WS-20 PROFESSIONAL EKF














STRIPS OUTER SHEATH FROM UP TO 18 mm ROUND AND FLAT CABLE














	Picture	Name	Multifunctional hand stripper WS-20 PROFESSIONAL EKF
SIONAL		Description	Multifunctional hand stripper WS-20, made in Germany, is designed for stripping outer PVC sheath from 6 to 13 mm round cables, flat cables up to 18 mm, and 0,5-6 mm² wire insulation. Easy to maneuver in tight and cramped spaces. Replaceable Solingen steel blades extend the life of the tool
PROFESSION		Cross-section, mm²	0,5-6
	H H H H H H H H H H H H H H H H H H H	Item code	ws-20
		Wire type	





EKF

AUTOMATIC WIRE STRIPPER WS-22 PROFESSIONAL EKF



















Picture	Name Automatic wire stripper WS-22 PROFESSIONAL EKF	
Descri	Description	Automatic wire stripper WS-22, made in Germany, works perfect for stripping insulation from 0,2-16 mm² wires. Thanks to its design, the tool automatically adjusts to any compatible wire type. The tool features graduated strip stop that can be adjusted up to 25 mm, as well as a built-in 3 mm wire cutter. Replaceable Solingen steel blades extend the life of the tool
	Cross-section, mm ²	0,2-16,0
J	Item code	ws-22
	Wire type	







MULTIFUNCTIONAL HAND STRIPPER WS-13 PROFESSIONAL EKF






















	Picture	Name	Multifunctional hand stripper WS-13 PROFESSIONAL EKF
PROFESSIONAL		Description	Multifunctional hand stripper WS-13, made in Germany, is designed to strip outer sheath from 8-13 mm cable and insulation from 0,5-6 mm² wires. Side cutter for working in tight spaces and buit-in knife for longitudinal cuts, built-in cutter for wires up to 6 mm in diameter
PROFES		Cross-section, mm²	0,5-6,0
_	2	Item code	ws-13
		Wire type	€ 🚭 😵 🚳 🔮





MULTIFUNCTIONAL HAND STRIPPER WS-16 PROFESSIONAL EKF















STRIPS OUTER 8-13 mm SHEATH, INNER 0,5-6 mm²

NON-ADJUSTABLE LONGITUDINAL CUT 3×1,5 mm²-5×2,5 mm²

10 POSITION
RETRACTABLE
AND REPLACEABLE
HOOK BLADE

HANDLE LOCK P

Picture	Name	Multifunctional hand stripper WS-16 PROFESSIONAL EKF
05 88 15 25 40 60	Description	Multifunctional hand stripper WS-16, made in Germany, is designed to strip outer sheath with both transverse and longitudinal cuts from 8-13 mm cable and insulation from 0,5-6 mm² wires. The tool features a 10-step adjustable cable knife with blade lock. Replaceable Solingen steel blade extend the life of the tool
	Cross-section, mm²	0,5-6,0
	Item code	ws-16
	Wire type	







MULTIFUNCTIONAL HAND STRIPPER WS-17 PROFESSIONAL EKF
















STRIPS
INSULATION
0,5-6 mm²
REPLACEABLE BLADES

BUILT-IN CUTTER FOR UP to 3 mm WIRES

	Picture	Name	Multifunctional hand stripper WS-17 PROFESSIONAL EKF
PROFESSIONAL		Description	Multifunctional hand stripper WS-17, made in Germany, is designed for stripping insulation from 0,5-6 mm² wires. Thanks to its design, the tool automatically adjusts to any compatible wire type. Easy to maneuver in tight and cramped spaces. The tool features two dedicated built-in crimpers for 0,5-6 mm² insulated and non-insulated cord end terminals as well as a 6 mm² wire cutter. Replaceable Solingen steel blades extend the life of the tool
PROFES	3	Cross-section, mm²	0,5-6,0
		Item code	ws-17
		Wire type	





WIRE STRIPPER COMPARISON: PROFESSIONAL

WIRE STRIPPERS

g		Wire stripping			O. Alima	
Item code	Picture	Round cable	Flat cable	Inner conductors	Cutting	Spare blade
<u>t</u> e		Diameter, mm	Width, mm	Conductor cross-section, mm ²	Diameter, mm	
WS-11	×	-	-	0,26	up to 2	slws-11
WS-14	R	-	up to 11	0,516	up to 3	slws-14
WS-22	K	-	-	0,216	up to 3	slws-22
WS-20		613	up to 18	0,56	-	slws-20
WS-13	H	813	-	0,56	up to 6	-
WS-16	1	613	-	0,56	-	slws-16
WS-17	H	-	-	0,56	up to 3	slws-17







CABLE STRIPPING KNIFE WS-12 PROFESSIONAL EKF













STEEL BRACE WITH HOOK BLADE









	Picture	Name	Cable stripping knife WS-12 PROFESSIONAL EKF
NAL		Description	Cable striping knife WS-12 is designed to quickly and accurately strip PVC sheaths from 4 to 28 mm cables using an integrated rotating eccentric blade, which enables a circular cross- or longitudinal cut of the cable sheath
PROFESSION		Diameter, mm	4-28
Ā	EKT PART OF THE PA	Item code	ws-12
		Wire type	€ 🚭 😵 🚳 🔮





EKF

CABLE STRIPPING KNIFE WS-15 PROFESSIONAL EKF
















TRANSVERSE CUTTING OF 4-28 mm ROUND CONDUCTORS

LONGITUDINAL CUTTING OF 4-28 mm ROUND CONDUCTORS

ADJUSTABLE DEPTH OF CUT +

HOOK BLADE LOCK IN THE EXTENDED POSITION

	Picture	Name	Cable stripping knife WS-15 PROFESSIONAL EKF
ONAL		Description	Cable stripping knife WS-15 is designed to quickly and accurately strip PVC sheaths from round cables 4 to 28 mm in diameter using the integrated rotating eccentric blade, which enables a circular cross- or longitudinal cut of the cable sheath
PROFESSIONAL	EKF	Diameter, mm	4-28
Ā		Item code	ws-15
		Wire type	€ 🚭 😵 🚱 🌑







CABLE STRIPPING KNIFE WS-18 PROFESSIONAL EKF

















BLADE CHANGE

	Picture	Name	Cable stripping knife WS-18 PROFESSIONAL EKF
ONAL		Description	Cable stripping knife WS-18 is designed to quickly and accurately strip outer PVC sheath from round cables 28 to 35 mm in diameter using the integrated rotating eccentric blade, which enables a circular cross- or longitudinal cut of the cable sheath
PROFESSIONAL		Diameter, mm	28-35
þ	Buck	Item code	ws-18
		Wire type	





ekfgroup.com

CABLE STRIPPING KNIFE WS-19 PROFESSIONAL EKF



















0,5 to 6 mn

	Picture	Name	Cable stripping knife WS-19 PROFESSIONAL EKF
ONAL	PROFESSIONAL	Description	Cable stripping knife WS-19 is designed to quickly and accurately strip outer PVC sheaths from round cables 4 to 28 mm in diameter using the integrated rotating eccentric blade, which enables a circular cross- or longitudinal cut of the cable sheath, as well as stripping of 0,5-6 mm² individual wires
ROFESSIO		Diameter, mm	4-28
Ы		Item code	ws-19
		Wire type	⊗ 🚭 😵 🚳 🔮







WIRE STRIPPERS

CABLE STRIPPING KNIVES PROFESSIONAL

ltem	Picture	Round cable stripping, mm	Conductor insulation stripping, mm²	Replaceable blade
WS-12	S Care	4-28	-	slws-12/18
WS-15	Exc.	4-28	-	slws-15/19
WS-18	Bix	28-35	-	slws-12/18
WS-19		4-28	0,5-6	slws-15/19

INSULATED CABLE KNIFE WITH GUIDE SHOE 1000V WS-31 PROFESSIONAL EKF


















PERMITS ANGLING
THE KNIFE TO MAKE
THE CUT EASIER

USE SAFETY GLOVES TO AVOID INJURY SMALLER GUIDE SHOE, TESTED TO WITHSTAND UP TO 1600 N OF FORCE

	Picture	Name	Insulated cable knife with guide shoe 1000V WS-31 PROFESSIONAL EKF
NAL		Description	Insulated cable knife with guide shoe 1000V WS-31 is designed to strip outer sheath and insulation from round and flat cables. Double-edged blade, to cut both towards and away from the user
	€ 1000 v	Item code	ws-31
		Wire type	
	Dicture	Name	Spudger Fasy Opener DROFFSSIONAL FKF

Picture	Name	Spudger Easy Opener PROFESSIONAL EKF
NAL	Description	Easy opener is designed to facilitate opening and disassembly of plastic housings and cases
PROFESSIONAL	Features	Does not scratch or damage the housing Flexible glass reinforced polyamide construction
ă	Wire type	easy-opener



CRIMPING PLIERS MASTER

	Picture	Name	Cross-section, mm²	Crimping profile	Item code
MASTER		Crimping pliers PK-16 MASTER EKF	1,5-16,0	Dimple (************************************	pk-16-mas-m
2	\$	Crimping pliers PK-35 MASTER EKF	2,5-35,0	Dimple (w)	pk-35-mas

ekfgroup.com ekfgroup.com 35



CRIMPERS

CRIMPERS

CRIMPING PLIERS EXPERT

EKF

	Picture	Name	Terminal type	Cross-section, mm ²	Crimping profile	Item code
		Crimping pliers PK-01 (0,5-6,0 mm² RV, SV, PTV, DBV) EXPERT EKF	RV, SV, PTV, DBV	0,5-6,0	Oval	pk-01-exp-m
		Crimping pliers PK-02 (0,25-6,0 mm² E, EN) EXPERT EKF	E, EN	0,25-6,0	Trapezoid	pk-02-exp-m
EXPERT		Crimping pliers PK-03 (4,0-16,0 mm² E, EN) EXPERT EKF	E, EN	4,0-16,0	Trapezoid	pk-03-exp-m
ũ		Crimping pliers PK-04 (0,5-6,0 mm² JGP) EXPERT EKF	JG	0,5-6,0	Automotive	pk-04-exp-m
		Crimping pliers PK-05 (0,5-10,0 mm² JG, GTY) EXPERT EKF	JG, GTY	0,5-10,0	Dimple	pk-05-exp-m
	A	Crimping pliers PK-06 (2×0,5-2×6,0 mm² TE) EXPERT EKF	TE	2×0,5-2×6,0	Trapezoid	pk-06-exp-m





CRIMPING PLIERS FOR INSULATED WIRE FERRULES

	Picture	Name	Term	inal type	Crimping	Item
	Picture	INdille	E, EN	TE	profile	code
		Crimping pliers PKV-6-4 EXPERT EKF	0,25-6,0	2×0,5-2×4	Square	pkv-6-4-exp-m
		Crimping pliers PKV-6-6 EXPERT EKF	0,25-6,0	2×0,5-2×4	Hexagon	pkv-6-6-exp-m
EXPERT		Crimping pliers PKV-16-4 EXPERT EKF	4,0-16,0	2×4-2×6	Square	pkv-16-4-exp-m
EX		Crimping pliers PKVt-16-4 EXPERT EKF	0,25-16,0	2×0,5-2×10,0	Square	pkvt-16-4-exp-m
		Crimping pliers PKVu-16-6 EXPERT EKF	0,25-16,0	2*0,5-2*6,0	Hexagon	pkvy-16-6-exp-m
	A	Crimping pliers PKV-70 EXPERT EKF	25,0-70,0	10,0-16,0	Two-point trapezoid	pkv-70-exp





CRIMPERS




EKF

MECHANICAL CRIMPING TOOLS

	Picture	Name	Mechanical crimping tool PK-50 EXPERT EKF	Mechanical crimping tool PK-120 EXPERT EKF
		Description	Mechanical crimping tool PK-50 is designed for manual crimping of aluminium and copper cable lugs and sleeves with the cross-section of 6-50 mm² using integrated rotating dies	Mechanical crimping tool PK-120 is designed for manual crimping of aluminium and copper cable lugs and sleeves with the cross-section of 10-120 mm ² using integrated rotating dies
		The rotating die desig	gn enables quick selection of the required size.	
		Cross-section, mm²	6, 10, 16, 25, 35, 50	10, 16, 25, 35, 50, 70, 95, 120
EXPERT	Λ	Terminal type	Hexagon	
		Weight, kg	1,4	3,8
	• •	Delivery scope	Mechanical crimping tool PK-50 Cardboard box	Mechanical crimping tool PK-120 Cardboard box
		Item code	pk-50-exp-m	pk-120-exp-m







Pict	ure	Name	Manual hydraulic crimping tool PGR-70 MASTER EKF	
		Description	Manual hydraulic crimping tool PGR-70 is designed for crimping aluminium and coppe cable lugs and sleeves with the cross-section from 4 to 70 mm²	
		Cross-section, mm ²	4, 6, 8, 10, 16, 25, 35, 50, 70. Interchangeable dies for quality crimping of thin-walled JG lugs	
4		Crimping profile	Hexagon	
HI E		Crimping force, tons	4,5	
		Net / Gross weight, kg	1,7 / 2,7	
		Delivery scope	Plastic case, set of dies, hydraulic crimping tool, technical manual, repair kit	
		Item code	pgr-70-m	
Picto	ure	Name	Manual hydraulic crimping tool PGR-120 MASTER EKF	
		Description	Manual hydraulic crimping tool PGR-120 is designed for crimping aluminium and copp cable lugs and sleeves with the cross-section from 10 to 120 mm²	
H		mm²	Cross-section, mm ²	10, 16, 25, 35, 50, 70, 95, 120. The dies have been improved for quality crimping of thin-walled JG lugs
127 - 164			Crimping profile	Hexagon
7		Crimping force, tons	6	
		Net / Gross weight, kg	2,7 / 4,3	
	R	Delivery scope	Plastic case, set of dies, hydraulic crimping tool, technical manual, repair kit	
		Item code	pgr-120-m	
Picto	ure	Name	Manual hydraulic crimping tool PGR-300 MASTER EKF	
		Description	Manual hydraulic crimping tool PGR-300 is designed for crimping aluminium and copposite cable lugs and sleeves with the cross-section from 10 to 300 mm²	
	r.	Cross-section, mm²	10, 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300. Interchangeable dies for quality crimping of thin-walled JG lugs	
i i		Crimping profile	Hexagon	

	Picture	Name	Manual hydraulic crimping tool PGR-300 MASTER EKF
		Description	Manual hydraulic crimping tool PGR-300 is designed for crimping aluminium and copper cable lugs and sleeves with the cross-section from 10 to 300 mm²
		Cross-section, mm ²	10, 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300. Interchangeable dies for quality crimping of thin-walled JG lugs
MASTER		Crimping profile	Hexagon
MAS		Crimping force, tons	7
		Net / Gross weight, kg	3,6 / 6,2
	II B	Delivery scope	Plastic case, set of dies, hydraulic crimping tool, technical manual, repair kit
		Item code	pgr-300-m



HYDRAULIC CRIMPING TOOLS EXPERT

	Picture	Name	Manual hydraulic crimping tool PGRs-70 EXPERT EKF		
		Description	Manual hydraulic crimping tool PGRs-70 is designed for crimping aluminium and copper cable lugs and sleeves with the cross-section from 4 to 70 mm². The model is equipped with a pressure limiting valve to prevent over-pressurization and preserve tool life		
		Cross-section, mm ²	4, 6, 8, 10, 16, 25, 35, 50, 70. The dies have been improved for quality crimping of thin-walled JG lugs		
ERT		Crimping profile	Hexagon		
EXPERT		Crimping force, tons	4,5		
	1/	Net / Gross weight, kg	1,8 / 2,8		
		Delivery scope	Plastic case, set of dies, hydraulic crimping tool, technical manual, repair kit		
		ltem code	pgrs-70-m		

	Picture	Name	Manual hydraulic crimping tool PGRs-120 EXPERT EKF
		Description	Hydraulic crimping tool PGRs-120 is designed for crimping aluminium and copper cable lugs and sleeves with the cross-section from 10 to 120 mm². The model is equipped with a pressure limiting valve to prevent over-pressurization and preserve tool life
		Cross-section, mm²	10, 16, 25, 35, 50, 70, 95, 120. The dies have been improved for quality crimping of thin-walled JG lugs
EXPERT		Crimping profile	Hexagon
EX		Crimping force, tons	6
		Net / Gross weight, kg	2,9 / 4,5
	B A	Delivery scope	Plastic case, set of dies, hydraulic crimping tool, technical manual, repair kit
		Item code	pgrs-120-m

	Picture	Name	Manual hydraulic crimping tool PGRs-300 EXPERT EKF	
		Description	Hydraulic crimping tool PGRs-300 is designed for crimping aluminium and copper cable lugs and sleeves with the cross-section from 10 to 300 mm². The model is equipped with a pressure limiting valve to prevent over-pressurization and preserve tool life	
		Cross-section, mm²	10, 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300. Interchangeable dies for quality crimping of thin-walled JG lugs	
EXPERT		Crimping profile	Hexagon	
Ä		Crimping force, tons	7	
		Net / Gross weight, kg	4,0 / 6,5	
		Delivery scope	Plastic case, set of dies, hydraulic crimping tool, technical manual, repair kit	
		Item code	pgrs-300-m	













Name

Tape measure RS-10 (3 m×16 mm) EXPERT EKF

Tape measure RS-10 (5 m×25 mm) EXPERT EKF

FLOATING HOOK



STRONGER MAGNETS







Length, m

3

5

AUTO-STOP


Item code

rs-10-3-16-quad

rs-10-5-25-quad



















EKF

INTEGRATED SPIRIT LEVEL FOR GREATER ACCURACY



BUILT-IN MEMORY FOR 20 MEASUREMENTS

Picture





	Name	Max. measurement range, m	Number of reference points	Accuracy, mm	ltem code
EXPERT	Laser distance meter LDM-50 EXPERT EKF	50			ldm-50
	Laser distance meter LDM-70 EXPERT EKF	70	2	± 2,0	ldm-70

42 43 ekfgroup.com ekfgroup.com

MULTIMETERS PROFESSIONAL

Model: MS18C

TRUERMS

Safety Rating: CAT III 1000V / CAT IV 600V













Basic functions

Measurement	Measuring range	Accuracy
Direct current voltage (DCV)	600 mV / 6 V / 60 V / 600 V / 1000 V	±0,5%±3D
Alternating current voltage (ACV)	6 V / 60 V / 600 V / 750 V	±1,0%±10D
Direct current (DCA)	60 μA / 60 mA / 600 mA / 20 A	±1,2%±3D
Alternating current (ACA)	60 mA / 600 mA / 20 A	±1,5%±3D
Electrical resistance $[\Omega]$	600 Ohm / 6 kOhm / 60 kOhm / 600 kOhm / 6 MOhm / 60 MOhm	±1,2%±30D
Capacitance	6 nF / 60 nF / 600 nF / 6 μF / 60 μF / 600 μF / 6 mF / 100 mF	±5,0%±3D
Frequency	9,999 Hz / 99,99 Hz / 999,9 Hz / 9,999 kHz	±1,0%±3D
Temperature (°C)	-20 °C 1000 °C	±1,0%±3D
Temperature (°F)	-4 °F 1832 °F	±1,0%±3D

D - least significant digit

Additional functions:

Diode test; transistor test; data hold; non-contact voltage detection; live circuit test; circuit continuity test (buzzer); display backlight; flashlight; automatic power off.

Delivery scope:

Multimeter - 1 pc. Set of probes (red/black) - 1 pc. Battery 1,5 V - 4 pcs. Thermocouple, type K - 1 pc. Technical and operation manual - 1 pc.



MULTIMETERS MASTER

Model: MAS830B Safety Rating: CAT III 600V











Basic functions

Measurement	Measuring range	Accuracy	
Direct current voltage (DCV)	200 mV / 2 V / 20 V / 200 V / 600 V	±0,8%±2D	
Alternating current voltage (ACV)	200 V / 600 V	±1,2%±10D	
Direct current (DCA)	200 μA / 2 mA / 20 mA / 200 mA / 10 A	±3,0%±10D	
Electrical resistance $[\Omega]$	200 Ohm / 2 kOhm / 20 kOhm / 200 kOhm / 2 MOhm	±1,0%±5D	

D - least significant digit

Additional functions:

Diode test Transistor test Data Hold

Delivery scope:

Multimeter - 1 pc. Set of probes (red/black) - 1 pc. Battery 9 V - 1 pc. Technical and operation manual - 1 pc.

Model: MAS830L Safety Rating: CAT III 600V











D - least significant digit





Basic functions

Measurement	Measuring range	Accuracy	
Direct current voltage (DCV)	200 mV / 2 V / 20 V / 200 V / 600 V	±0,8%±5D	
Alternating current voltage (ACV)	200 V / 600 V	±1,2%±10D	
Direct current (DCA)	200 μA / 2 mA / 20 mA / 200 mA / 10 A	±3,0%±10D	
Electrical resistance $[\Omega]$	200 Ohm / 2 kOhm / 20 kOhm / 200 kOhm / 2 MOhm	±1,0%±5D	

Additional functions:

Diode test Transistor test Data Hold Circuit continuity test (buzzer) Display backlight

Delivery scope:

Multimeter - 1 pc. Set of probes (red/black) - 1 pc. Battery 9 V - 1 pc. Technical and operation manual - 1 pc.







In-180701-pm18C

In-180701-pm8211

MULTIMETERS EXPERT

Model: MS8211 Safety Rating: CAT III 600V





Basic functions

Measurement	Measuring range	Accuracy
Direct current voltage (DCV)	200 mV / 2 V / 20 V / 200 V / 600	±0,8%±5D
Alternating current voltage (ACV)	2V/20V/200V/600V	±1,0%±5D
Direct current (DCA)	20 mA / 200 mA	±1,8%±5D
Alternating current (ACA)	20 mA / 200 mA	±2,0%±5D
Electrical resistance (Ω)	200 Ohm / 2 kOhm / 20 kOhm / 200 kOhm / 2 MOhm / 20 MOhm	±1,2%±15D

D - least significant digit

Additional functions:

Diode test
Circuit continuity test (buzzer)
Data Hold
Non-contact voltage detection
Display backlight
Integrated flashlight
Auto power off

Delivery scope:


Multimeter - 1 pc.
Battery 1,5 V - 2 pcs.
Bag - 1 pc.
Technical and operation manual - 1 pc.







MULTIMETER COMPARISON



In-180701-pm830B

In-180701-pm830L

Item code





PROBES

	Picture	Name	Maximum Current, A	Lead length, mm	Item code
		Alligator clip set TLA3102 EXPERT EKF	10	-	TLA3102
EXPERT		Set of probes TL3001 (1 m) (20AWG) EXPERT EKF	10	1000	TL3001
		Set of probes TL3006 (1,2 m) (18AWG) EXPERT EKF	10	1200	TL3006

WARNING! Black probe is plugged into the common socket, red probe is plugged into the + socket.





E-RESIST MS2302 PROFESSIONAL EKF











VOLTAGE MEASUREMENT (CATIII 1000V)

BACKLIT DISPLAY BATTERY INDICATOR

TWO/THREE WIRE MEASUREMENT

SIX AA BATTERIES

	Earthing resistance measurement		
Range Absolute error Resolutio			
0 ÷ 29,99 Ohm	± [2 % + 6 LSD]	0,01 Ohm	
30,0 ÷ 99,9 Ohm	± (3 % + 3 LSD)	0,1 Ohm	
100 ÷ 999 Ohm	1 Ohm		
1,00 ÷ 4,00 kOhm	10 Ohm		
	Voltage		
Range Absolute error Resoluti			
0 ÷ 600 V (50 / 60 Hz)	± (1 % + 5 LSD)		

Delivery scope:

Device - 1 pc.
Probes - 3 pcs. (red - 15 m, green - 10 m, black - 5 m)
Aux. terminal bars - 2 pcs.
Aligator clip - 1 pc.
Carry bag - 1 pc. AA battery - 6 pcs. Technical manual - 1 pc.

49 48 ekfgroup.com ekfgroup.com



Model: MS2016S Safety Rating: CAT III 600V





Basic functions

Measurement	Measuring range	Accuracy
Direct current voltage (DCV)	600 V	±0,5%±3D
Alternating current voltage (ACV)	600 V	±0,8%±5D
Alternating current (ACA)	6 A/ 60 A / 200 A	±2,5%±8D
Electrical resistance (Ω)	6 kΩ	±0,8%±3D
Frequency	60 Hz / 1000 Hz	±1,0%±5D

D - least significant digit

51

Additional functions:

Circuit continuity test (buzzer) Data Hold Non-contact voltage detection Display backlight Auto range selection Auto power off

Delivery scope:

Clamp meter - 1 pc. Set of probes (red/black) - 1 pc. Battery 1,5 V - 2 pcs. Carry bag - 1 pc. Technical and operation manual - 1 pc.

CLAMP METERS EXPERT EKF

Model: 266C

CLAMP

METERS

EKF

Safety Rating: CAT II 1000V, CAT III 600V











Basic functions

Measurement	Measuring range	Accuracy
Direct current voltage (DCV)	200 mV / 2 V / 20 V / 200 V / 1000 V	±0,8%±3D
Alternating current voltage (ACV)	200 V / 750 V	±1,2%±5D
Alternating current (ACA)	20 A / 200 A / 1000 A	±3,0%±10D
Electrical resistance (Ω)	200 Ohm / 2 kOhm / 20 kOhm / 200 kOhm / 2 MOhm	±1,0%±8D
Temperature (°C)	0 to 750 °C	±1,0%±3D
Temperature (°F)	32 to 1832 ℉	±1,0%±3D

D - least significant digit

Additional functions:

Circuit continuity test (buzzer) Data Hold

Delivery scope:

Clamp meter - 1 pc. Set of probes (red/black) - 1 pc. Thermocouple, type K - 1 pc. Battery 9 V - 1 pc. Bag - 1 pc. Technical and operation manual - 1 pc.





50 ekfgroup.com ekfgroup.com



DIGITAL CLAMP METER COMPARISON

	C INH	
Name	M266C	MS2016S
Manufacturer	EKF	EKF
Product line	EXPERT	EXPERT
Safety level	CATII 1000 V CAT III 600 V	CAT III 600 V
Digit capacity	1999	6000
Automatic mode selection	-	•
Automatic measurement range selection	-	•
DC voltage	1000 V	600 V
AC voltage	750 V	600 V
Voltage measurement with low input impedance LOWz	-	-
Direct current, A	-	-
Alternating current	1000 A	200 A
Resistance	20 MOhm	0,006 MOhm
Capacitance	-	-
Frequency	-	0,001 MHz
Temperature	750 °C	-
Relative pulse duration	-	-
Diode test	-	-
Continuity test	•	•
hFE transistor check	-	-
True RMS	-	-
Relative measurement	-	-
DATA HOLD function	•	•
Max/Min values	-	-
Non-contact voltage detection (NCV)	-	•
Backlit display	-	•
Integrated flashlight	-	-
Auto power off	-	•
Weight (with batteries), g	330	150
Overall dimensions (W×H×D), mm	96×235×46	53×158×28
ltem code	In-180702-pc266C	In-180702-pc2016S





PYROMETER

Model: MS6519A /MS6519B










Characteristics	Values			
Model	MS6519A MS6519B			
Product line	EXP	ERT		
Display	Color	·LCD		
D:S ratio	12	2:1		
Emissivity range	0,10-	-1,00		
Wavelength, µm	8-	14		
Laser	Class 2, < 1 mW / 630-670 nm			
Response time, s	< 0,5			
Auto power off, s	30			
Operating temperature, °C	0 to 40			
Storage temperature, °C	-10 t	to 60		
Temperature measurement range, °C	-50 to 0 (±3) / 0 to +380 ± (1.5% +2)	-50 to 0 (±3) / 0 to +550 ± (1.5% +2)		
Power supply	2×1,5	VAAA		
Weight, g / Dimensions, mm	200 / 165	5×100×46		
Accuracy (non-contact measurement), °C	-50 to 0 (± 3°C) 0 to 300 ±(1,5%+2°C)			
Service life, years	10			
Item code	In-180703-pt6519A In-180703-pt6519B			



Additional functions:

Measurement and recording of maximum values Data Hold Display backlight Auto power off

Delivery scope:

Infrared thermometer (pyrometer) - 1 pc. Battery 1,5 V - 2 pcs. Technical manual - 1 pc.



LAN AND TELECOM TOOLS



Picture	Name	Punch down tool TRC-S50 TERACOM EKF
-6°	Description	Designed to trim and insert the wires into insulation-displacement connectors on punch down blocks, patch panels, keystone modules, and surface mount boxes.
See and the second	Features	Termination of 110 (DUAL) and KRONE connections Built in hook and prier for wire extraction Scissor mechanism for trimming excess wire during insertion
*	Item code	TRC-S50
Picture	Name	Punch down tool TRC-S50 TERACOM EKF
	Description	Designed for insertion and connection of twisted pair wires to IDC terminals on cross panels and patch panels, keystone modules and biscuit jacks in order to build structured cabling systems.
To the second se	Features	 Interchangeable dual-sided 110 / KRONE blade Single-step insertion/trimming action Adjustable spring force Spare blade compartment
•	Item code	TRC-S55
	ı	
Picture	Name	Multifunctional coax cable stripper TRC-S10 TERACOM EKF
	Description	Compact multifunctional stripper, designed to strip insulation from different gauges and types of coaxial cable (RG58, RG59, RG6, RG174)
Non A	Features	 Rotating die for selecting appropriate cable type Adjustable 4-12 mm cut depth Finger ring for a comfortable circular cut Cut depth can be adjusted using a hex key (included)
	Item code	TRC-S10
	·	
Picture	Name	Multifunctional UTP/STP stripper TRC-S11 TERACOM EKF
P.	Description	Multifunctional stripper, designed for cutting and removing outer cable sheath and insulation from twisted pair cables (UTP/STP) as well as telephone cable 3,5 to 9,0 mm in diameter
Control of the second s	Features	Cuts cables and individual twisted pair wires Two blades for stripping flat cables Two slots for stripping round cables Strip depth adjustment screw
	Item code	TRC-Sti
	· · · · · · · · · · · · · · · · · · ·	







LAN AND TELECOM TOOLS

Picture	Name	Crimper TRC-NT10 TERACOM EKF
	Description	Multifunctional crimper for RJ45 (8P8C), RJ12 (6P6C), RJ11 (6P4C), and 6P2C jacks, as well as cutter and stripper of cables for voice and data applications
9.30	Features	 Reliable crimping of RJ45, RJ12, RJ11, 6P2C jacks Built-in blades for uniform cutting and stripping of individual wires Ratchet mechanism with safety release Compatible with AWG 23 to AWG 28 wires Rubberized non-slip handles
	Item code	TRC-NT10
Picture	Name	Crimper TRC-NT20 TERACOM EKF
a de la constantina della cons	Description	Multifunctional crimper for RJ45 (8P8C), RJ12 (6P6C), and RJ11 (6P4C) jacks, as well as cutter and stripper of cables for voice and data applications
	Features	 Reliable crimping of RJ45, RJ12, RJ11 jacks Built-in blades for uniform cutting and stripping of individual wires Ratchet mechanism with safety release Compatible with AWG 23 to AWG 28 wires Rubberized non-slip handles
	Item code	TRC-NT20
Picture	Name	Crimper TRC-NT12 TERACOM EKF
	Description	Multifunctional crimper for 8P8C (RJ45), 6P6C (RJ12), 6P4C (RJ11), 6P2C, 4P4C, 4P2C jacks, as well as cutter and stripper of cables for voic and data applications
	Features	 Reliable crimping of RJ45, RJ12, RJ11 6P2C, 4P4C, 4P2C jacks Built-in blades for uniform cutting and stripping of individual wires Compatible with AWG 23 to AWG 28 wires Complimentary manual punch down tool (110 / KRONE)









ABC INSTALLATION ACCESSORIES

ABC INSTALLATION ACCESSORIES



	Picture	Name	Universal dielectric socket wrench for ABC clamps MK EKF
EXPERT		Description	Designed for torquing down shear bolt heads on ABC branching clamps. Suitable for live work
		Features	Max. torque - 24 Nm 1000 V insulation Wrench size - 10, 13, 17, 22 mm
		Item code	mk-160-abc

	Picture	Name	Come-along grip CT105.20 (3-22mm) EKF
EXPERT		Description	Used to adjust overhead line wires, the lever device converts the pulling force into a gripping force
		Features	Cable diameter: 4 - 22 mm Max. load - 2 tonnes Does not damage insulation
		Item code	ct-105.20

	Picture	Name	Swivel CT134 EKF
t.	t .	Description	Used to prevent the ABC wire bundle from unwinding when unrolling. The swivel is mounted between the pulling grip and the leader wire rope
EXPERT		Features	Compact dimensions and cylindrical shape prevent the bundle of ABC wires from unrolling Working load - 30 kN Max. leader wire rope diameter - 16 mm
		Item code	ct-134

	Picture	Name	Steel band tensioning and cutting tool INRSL-01 EKF
		Description	Intended for tightening and cutting 20 mm wide and up to 1 mm thick stainless steel bands
EXPERT		Features	The band is used for the installation of overhead line assemblies as well as the packaging of various loads and goods (stacks of boards, pallets of bricks etc.), installation of road signs, signboards, stretchers, etc. Automatic clamping device enables the use of different band thicknesses. High-quality materials of the tool ensure long service life
		Item code	ct-42.01

	Picture	Name	Steel band tensioning and cutting tool with ratchet mechanism INRSL-02 EKF
EXPERT		Description	Designed for tightening and cutting 20 mm wide and up to 1 mm thick steel band
		Features	Designed for tensioning the rim band when installing hooks and distant rim on metal, wooden or reinforced concrete supports. Built-in cutter to trim the excess band Ratchet mechanism for faster band pull-through Hardened steel working part
		Item code	ct-42.02

	Picture	Name	Cable Puller Sheave RM50 EKF
L		Description	Cable Puller Sheave is used to string ABC through straight runs and gentle turns of up to 30°. It is hanged on intermediate supports via an integrated hook
EXPERT		Features	The roller reel is made of glass-reinforced polyamide, ensuring excellent wear resistance and electrical insulation The roller frame is made of galvanized steel
		Item code	rm-50

EXPERT	Picture	Name	Manual ratcheting winch ST-116 (1500 kg) EKF
		Description	Used for tensioning ABC and fiber-optic cables, the winch is designed for transferring the cable from the stringing roller to anchoring and supporting clamps
		Features	Diameter of steel wire rope: 6 mm Maximum load with block and tackle (1,6 m): 1500 kg Maximum load without block and tackle (3 m): 750 kg
		Item code	st-116

	Picture	Name	Splitting wedges ST31 EKF
		Description	Used to separate the conductor from the ABC bundle during installation of clamps and terminals
EXPERT		Features	Manufactured from high-strength polymer with excellent insulating properties Comfortable knurled wedge handles prevent slipping when working No damage to ABC wire insulation Mechanical deformation limit - 80 kg
		Item code	st-31

	Picture Picture	Name	Wire brush, plastic handle, 5 rows EKF
ᅜ	THE REAL PROPERTY OF THE PERSON OF THE PERSO	Description	Intended for cleaning off or removing rust and paint from steel surfaces
EXPE		Features	Steel wire brush for optimal function, durability, and longer service life Angled plastic handle for more comfortable use
		Item code	wbs-pl-5-exp
	Picture	Name	Cable tie gun tensioning and cutting tool TTC210 EKF
EXPERT	6-0	Description	Designed for tensioning and cutting non-reusable cable ties 2,4 - 9,0 mm wide
Ä		Features	Significantly reduces installation time Ensures the required tensioning force

Item code





ttc-210

ekfgroup.com ekfgroup.com 59



DIRECT FASTENING TECHNOLOGY



NAILS

Picture	Name	Nail type / Coating	Dimensions, mm (diameter x length)	Item code
	Steel/Concrete nails CN collated forged ballistic point galvanized 17×3 mm (1000 pcs.) EKF		3,0×17	cpn-3017bp
	Steel/Concrete nails CN collated forged ballistic point galvanized 19×3 mm (1000 pcs.) EKF		3,0×19	cpn-3019bp
	Steel/Concrete nails CN collated forged ballistic point galvanized 22×3 mm (1000 pcs.) EKF	Reinforced, ballistic tip,	3,0×22	cpn-3022bp
688888888	Steel/Concrete nails CN collated forged ballistic point galvanized 25×3 mm (1000 pcs.) EKF	galvanized	3,0×25	cpn-3025bp
	Steel/Concrete nails collated forged ballistic point galvanized 32×3 mm (250 pcs.) EKF		3,0×32	cpn-3032bp
	Steel/Concrete nails CN collated forged ballistic point galvanized 38×3 mm (250 pcs.) EKF		3,0×38	cpn-3038bp
	Steel/Concrete/Brickwork nails CN collated 17×2,7 mm [1000 pcs.] EKF		2,7×17	cpn-2717bg
	Steel/Concrete/Brickwork nails CN collated 19×2,7mm [1000 pcs.] EKF	Standard,	2,7×19	cpn-2719bg
444444444	Steel/Concrete/Brickwork nails CN collated 22×2,7 mm [1000 pcs.] EKF	blued	2,7×22	cpn-2722bg
	Steel/Concrete/Brickwork nails CN collated 25×2,7 mm [1000 pcs.] EKF		2,7×25	cpn-2725bg

Picture	Name	Contents	Item code
		Steel/Concrete/Brickwork nails CN collated 17×2,7 mm	
	Steel/Concrete/Brickwork	Steel/Concrete/Brickwork nails CN collated 19×2,7 mm	
		Steel/Concrete/Brickwork nails CN collated 22×2,7 mm	
mmm		Steel/Concrete/Brickwork nails CN collated 25×2,7 mm	
		Steel/Concrete nails CN collated forged ballistic point galvanized 17×3 mm	1
	nails combo pack No. 1 CN EKF	Steel/Concrete nails CN collated forged ballistic point galvanized 19×3 mm	cp-cn1-1
		Steel/Concrete nails CN collated forged ballistic point galvanized 22×3 mm	
		Steel/Concrete nails CN collated forged ballistic point galvanized 25×3 mm	
		Steel/Concrete nails CN collated forged ballistic point galvanized 32×3 mm	
		Steel/Concrete nails CN collated forged ballistic point galvanized 38×3 mm	







SURFACE-MOUNTED JUNCTION BOXES









FOR OD 11 mm
NAILER TIPS

MEMBRANE CABLE
ENTRY GASKETS
WITH TALLER STEPS

LARGER GASKET RETAINING RINGS FOR A SECURE FIT IN THE JUNCTION BOX

Picture	Name	Retail sticker	Length×width× hight, mm	Item code
	Junction box KMP-030-014 (100×100×50) with cover,	-	100×100×50	plc-kmr-030-014
000	for direct mounting, 10 membrane entries, grey IP55 EKF	Yes Yes		plc-kmr-030-014-r
N	Junction box KMP-030-031 (85×85×40) with cover,	-	85×85×40	plc-kmr-030-031
000	for direct mounting, 8 membrane entries, grey IP55 EKF		85^85^40	plc-kmr-030-031-r
1000	Junction box KMP-030-034 (100×100×50) with cover, for direct mounting, cutout cable entries, grey IP54 EKF	-	100×100×50	plc-kmr-030-034
100	Junction box KMP-030-035 (85×85×40) with cover, for direct mounting, cutout cable entries, grey IP54 EKF	-	85×85×40	plc-kmr-030-035
000	Junction box KMP-030-014 (100×100×50) with cover, for direct mounting, 10 membrane entries, black IP55 EKF	-	100×100×50	plc-kmr2-030-014-b
000	Junction box KMP-030-014 (100×100×50) with cover, for direct mounting, 8 membrane entries, black IP55 retail sticker EKF	Yes	100×100×50	plc-kmr-030-014-b
000	Junction box KMP-030-031 (85×85×40) with cover, for direct mounting, 8 membrane entries, black IP55 EKF	-	85×85×40	plc-kmr2-030-031-b
000	Junction box KMP-030-031 (100×100×50) with cover, for direct mounting, 10 membrane entries, black IP55 retail sticker EKF	Yes	85×85×40	plc-kmr-030-031-b
000	Equipotential bonding terminal box KUP-030-014 with cover surface-mounted (100×100×50) 10 membrane cable entries IP55 EKF	-	100×100×50	plc-kmr-030-014-g
000	Equipotential bonding terminal box KUP-030-031 with cover surface-mounted (100×100×50) 8 membrane cable entries IP55 EKF	_	85×85×40	plc-kmr-030-031-g





DIRECT FASTENING CONDUIT CLIPS











SNUGLY FITS THE NAILER TIP

MOLDED BASE NUBS TO MAKE CENTERING EASIER

SMALLER OPENING DIAMETER TO PREVENT STRIKETHROUGH

DOVETAIL ON TOP AND BOTTOM OF THE CLIP FOR GANGABLE INSTALLATION

Picture	Name	Color	Item code
	Direct fastening conduit clip d=16 mm (100 pcs.) grey EKF-Plast	Grey	derjp-z-16
	Direct fastening conduit clip d=20 mm (100 pcs.) grey EKF-Plast	Grey	derjp-z-20
	Direct fastening conduit clip d=25 mm (100 pcs.) grey EKF-Plast	Grey	derjp-z-25
	Direct fastening conduit clip d=16 mm (100 pcs.) black EKF-Plast	Black	derjp-z-16-black
41	Direct fastening conduit clip d=20 mm (100 pcs.) black EKF-Plast	Black	derjp-z-20-black
	Direct fastening conduit clip d=25 mm (100 pcs.) black EKF-Plast	Black	derjp-z-25-black
	Direct fastening conduit clip d=16 mm (100 pcs.) orange EKF-Plast	Orange	derjp-z-16o
	Direct fastening conduit clip d=20 mm (100 pcs.) orange EKF-Plast	Orange	derjp-z-20o
	Direct fastening conduit clip d=25 mm (100 pcs.) orange EKF-Plast	Orange	derjp-z-25o







DIRECT FASTENING CABLE TIE MOUNTS











CROSS-MOULDINGS FOR A SNUG FIT ON THE 11 mm NAILER TIP

ADDITIONALLY, CROSS-MOULDINGS HELP TO DAMPEN THE NAIL STRIKE

SOLID BACK FOR EFFORTLESS CABLE TIE INSERTION









DOUBLE REINFORCED MOUNTING HOLE AREA TO PREVENT STRIKETHROUGH

WIDE BASE

BASE NUBS TO LEVEL AND CENTER THE CABLE TIE MOUNT

Picture	Name	Cable tie opening size, mm	Color	Item code
70	Direct fastening cable tie mount grey (100 pcs.) EKF	9	Grey	pdm-g
	Direct fastening cable tie mount black (100 pcs.) EKF	9	Black	pdm-b

TEXTILE MOUNTING TAPE





CARDBOARD BOX WITH CONVENIENT TAPE PULL OPENING ON THE TOP







Picture	Name	Length, m	Width, mm	Item code
	Textile mounting tape 20 mm (25 m) EKF	25	20	tmt-20-25

STEEL CONDUIT STRAPS







STIFFENERS FOR EXTRA DURABILITY

HIGH-QUALITY GALVANIZED STEEL

Picture	Name	Diameter, mm	Item code
		8-9	smp-1-8-9
	Direct fastening one-hole conduit strap (100 pcs.) EKF	12-13	smp-1-12-13
		14-15	smp-1-14-15
and the same of th		16-17	smp-1-16-17
-TP		19-20	smp-1-19-20
The state of the s		21-22	smp-1-21-22
		25-26	smp-1-25-26
	Direct fastening one-hole conduit strap (50 pcs.) EKF	31-32	smp-1-31-32
		38-40	smp-1-38-40
		48-50	smp-1-48-50
		8-9	smp-2-8-9
	Direct fastening two-hole conduit strap (100 pcs.) EKF	12-13	smp-2-12-13
		14-15	smp-2-14-15
		16-17	smp-2-16-17
- 600		19-20	smp-2-19-20
TO Y		21-22	smp-2-21-22
200		25-26	smp-2-25-26
		31-32	smp-2-31-32
-	Direct fastening two-hole	38-40	smp-2-38-40
	conduit strap (50 pcs.) EKF	48-50	smp-2-48-50
		60-63	smp-2-60-63

DIRECT FASTENING CABLE HOLDERS



DOUBLE-SIDED 16-CABLE HOLDER


SINGLE-SIDED 8-CABLE HOLDER

Picture	Name	Maximum cable diameter, mm	Length, mm	Item code
	Double-sided cable holder for direct mounting grey (20 pcs.) EKF	10	240	ch-2-g-240
2	Single-sided cable holder for direct mounting grey (20 pcs.) EKF	10	145	ch-1-g-145
	Double-sided cable holder for direct mounting black (20 pcs.) EKF	10	240	ch-2-b-240
	Single-sided cable holder for direct mounting black (20 pcs.) EKF	10	145	ch-1-b-145

65 64 ekfgroup.com ekfgroup.com



	Conc	 rete, Reinf	(∯ Concrete, Reinforced concrete	crete		Solid bricks	ricks			Hollow bricks) oricks							
Compatible and recommended nail sizes	Lean cc (B10-	Lean concrete (B10-B25)	Rich concrete (B30-B45)	ncrete B45)	Ceramic	mic	Calcium Sllicate	Sllicate	Ceramic	mic	Calcium Sllicate	Sllicate	Foam concrete	ncrete	Sand / Cement screed	Sement	Steel	<u></u>
ror dirrerent materials	lsmitqO	Suitable	lsmitqO	Suitable	lsmitqO	Suitable	Optimal	Suitable	lsmitq0	Suitable	Optimal	Suitable	lsmitq0	Suitable	lsmitq0	Suitable	lsmitq0	Suitable
Cable holder	2,7×19 2,7×22	3×19 3×22	3×19 3×22	ı	3×19 3×22	ı	3×19 3×22	ı	3×22 3×25	2,7×22 2,7×25	2,7×22 2,7×25	3 × 2 2 2 3 × 2 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	2,7×22 2,7×25	3 × × × × × × × × × × × × × × × × × × ×	ı	ı	2,7×17 2,7×19	3×17 3×19
Modern Dox	2,7×19 2,7×22	3×19 3×22	3×19 3×22	ı	3×19 3×22	ı	3×19 3×22	ı	3×22 3×25	2,7×22 2,7×25	2,7×22 2,7×25	3×22 3×25	2,7×22 2,7×25	3×2 3×25 5×25	ı	ı	2,7×17 2,7×19	3×17 3×19
Textile mounting tape	2,7×17 2,7×19	3×19 3×22	3×17 3×19	ı	3×17 3×19	ı	3×17 3×19	ı	3 × 22 3 × 25	2,7×22 2,7×25	2,7×22 2,7×25	3 × 2 2 3 × 2 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	2,7×19 2,7×22	3×19 3×22	2,7×22 2,7×25	3×22 3×25	2,7×17 2,7×19	3×17 5×19
Steel banding	2,7×17 2,7×19	3×17 3×19	3×17 3×19	ı	3×17 3×19	ı	3×17 3×19	ı	3 × 22 3 × 25	2,7×22 2,7×25	2,7×22 2,7×25	3 × 2 × 3 × 5 × 5 × 5 × 5 ×	2,7×19 2,7×22	3×19 3×22	2,7×22 2,7×25	3×22 3×25	2,7×17 2,7×19	3×17 5×19
Perforated steel	2,7×17 2,7×19	3×17 3×19	3×17 3×19	ı	3×17 3×19	ı	3×17 3×19	ı	3 × 22 3 × 25	2,7×22 2,7×25	2,7×22 2,7×25	3 × × × × × × × × × × × × × × × × × × ×	2,7×19 2,7×22	3×19 3×22	2,7×22 2,7×25	3×22 3×25	2,7×17 2,7×19	3×17 5×19
Cable tie mount	2,7×19 2,7×22	3×19 3×22	3×19 3×22	ı	3×19 3×22	ı	3×19 3×22	ı	3 × 22 3 × 25	2,7×22 2,7×25	2,7×22 2,7×25	3 × × 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	2,7×22 2,7×25	3 3 2 2 2 2 3 2 3 2 3 2	ı	ı	2,7×17 2,7×19	3×17 3×19
Conduit clip	2,7×19 2,7×22	3×19 3×22	3×19 3×22	ı	3×19 3×22	1	3×19 3×22	ı	3 × 22 3 × 25	2,7×22 2,7×25	2,7×22 2,7×25	3 × 2 2 3 × 2 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	2,7×22 2,7×25	3 × 2 × 3 × 5 × 5 × 5 × 5 ×	ı	ı	2,7×17 2,7×19	5 × 5 × 5 × 5
Steel conduit strap	2,7×17 2,7×19	3×17 3×19	3×17 3×19	ı	3×17 3×19	ı	3×17 3×19	ı	3×22 3×25	2,7×22 2,7×25	2,7×22 2,7×25	3 × × 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	2,7×19 2,7×22	3×19 3×22	ı	ı	2,7×17 2,7×19	5×5 7×5 61×5
Aluminium profile	2,7×17 2,7×19	3×17 3×19	3×17 3×19	ı	3×17 3×19	ı	3×17 3×19	ı	3×22 3×25	2,7×22 2,7×25	2,7×22 2,7×25	3 × × 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	2,7×19 2,7×22	3×19 3×22	2,7×22 2,7×25	3 × 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	2,7×17 2,7×19	3×17 71×5
M Aluminium hanger	2,7×17 2,7×19	3×17 61×5	3×17 3×19	ı	3×17 3×19		3×17 3×19		3 × 22 3 × 25	2,7×22 2,7×25	2,7×22 2,7×25	3 × 2 × 3 × 3 × 3 ×	2,7×19 2,7×22	3×19 3×22	ı	ı	2,7×17 2,7×19	5. 5. 6. 7. 7.
Electrical box drilling template	3×25 3×32	2,7×25	3×25 3×32	ı	3×32 3×32	2,7×25	3×2 3×32	2,7×25	3×25 3×32	ı	3×25 3×32	ı	2,7×25	3×2 3×32 3×32	ı	ı	2,7×25	3×17 3×19
Plywood, 10 mm	3×32 3×38	ı	3×32 3×38	ı	3×32 3×38	ı	3 × 32 3 × 38	ı	3×38	ı	3×38	ı	3×32 3×38	ı	ı	ı	ı	ı
Parapet cable duct	2,7×17 2,7×19	3 × 5 7 × 5 7 × 7	3×17 3×19	1	3×17 01×5	1	3×17 8×19	ı	3 × × 22 × 25 × 25	2,7 × 22 2,7 × 25	2,7×22 2,7×25	8 8 8 8 8 8 8 8	2,7×19 2,7×22	3×19 3×22	1	1	2,7×17 2,7×19	5 × 5 71 × 6





CORE DRILL BITS

DIAMOND CORE DRILL BITS FOR ELECTRICAL BOXES











QUICK CENTERING BIT REMOVAL SYSTEM CUTTERS

STANDARD / TURBO FAST MODELS

HIGHER DIAMONDS CONTENT

CAUTION! DO NOT USE WITH IMPACT DRILLS IN IMPACT MODE

	Picture	Name	Outer diameter, mm	Number of cutters	Arbor	Cutting depth, mm	Item code
		Diamond core drill bit DCH-68 Laser M16 SDS-Plus EXPERT EKF	68	5			dch-68-m16
		Diamond core drill bit DCH-72 Laser M16 SDS-Plus EXPERT EKF	72	3			dch-72-m16
EXPERT		Diamond core drill bit DCH-82 Laser M16 SDS-Plus EXPERT EKF	82	6	Mi6	72	dch-82-m16
_	<u></u>	Diamond core drill bit Turbo Fast 68 DCH-68TRB Laser M16 EXPERT EKF	68	5	MIO	72	dch-68-trb-m16
		Diamond core drill bit Turbo Fast 72 DCH-72TRB Laser M16 EXPERT EKF	72	3			dch-72-trb-m16
	_	Diamond core drill bit Turbo Fast 82 DCH-82TRB Laser M16 EXPERT EKF	82	6			dch-82-trb-m16

CORE DRILL BITS













COMPATIBLE WITH MICRO-HIT ROTARY HAMMERS

LASER WELDED CUTTERS

TOPSIDE DUST EXTRACTION MODELS

HIGHER DIAMONDS CONTENT

	Picture	Name	Outside diameter, mm	Number of cutters	Drill depth, mm	Arbor	ltem code
		Diamond core drill bit for micro-impact drills DCH-68MH Micro Hit Laser M16 PROFESSIONAL EKF	68				dch-68-mh-m16
		Diamond core drill bit for micro-impact drills DCH-72MH Micro Hit Laser M16 PROFESSIONAL EKF	72	6			dch-72-mh-m16
PROFESSIONAL		Diamond core drill bit for micro-impact drills DCH-82MH Micro Hit Laser M16 PROFESSIONAL EKF	82	7	70	Mic	dch-82-mh-m16
PRO		Diamond core drill bit for micro-impact drills (top dust extraction) DCH-68MHS Micro Hit Laser M16 PROFESSIONAL EKF	68		72	M16	dch-68-mhs-m16
		Diamond core drill bit for micro-impact drills (top dust extraction) DCH-72MHS Micro Hit Laser M16 PROFESSIONAL EKF	72	6			dch-72-mhs-m16
		Diamond core drill bit for micro-impact drills (top dust extraction) DCH-82MHS Micro Hit Laser M16 PROFESSIONAL EKF	82	7			dch-82-mhs-m16





ekfgroup.com ekfgroup.com 69



CORE DRILL BITS

CORE DRILL BITS FOR ELECTRICAL BOXES

EKF

	Picture	Name	Outer diameter, mm	Number of cutters, pcs	Shank	Arbor	Drill depth, mm	Item code
1ASTER		Carbide core drill bit with accessories TCT-68 M22 SDS-plus MASTER EKF	68	8	000 mbs	M00	50	tct-68-m22
Σ		Carbide core drill bit with accessories TCT-72 M22 SDS-plus MASTER EKF	72	8	SDS-plus	M22	50	tct-72-m22





CORE DRILL BIT ACCESSORIES

	Picture	Name	Item code
		Adapter Hex/M16 with centering drill bit EXPERT EKF	ad-hex
		Adapter SDS-plus/M16 with centering drill bit EXPERT EKF	ad-sdsplus
		Adapter for diamond core drill bits (M18-M16) EXPERT EKF	ad-m18-m16
EXPERT	l lekr	Adapter for diamond core drill bits (M22-M16) EXPERT EKF	ad-m22-m16
		Dust extractor for diamond core drill bit (M16-M18) EXPERT EKF	dd-exp
		Dust extractor (Mi6-M22) EXPERT EKF	dd-exp-m16-m22
		Centering bit for dust extractor EXPERT EKF	cdd-exp

DIAMOND CORE DRILL BITS

CORE DRILL BITS











THREADED CONNECTION 1 1/4" UNC

SUITABLE FOR WET DRILLING

LASER WELDED DIAMOND CUTTERS

PROFILED DIAMOND CUTTERS

	Picture	Name	Drill depth, mm	Outer diameter, mm	Shank	Number of cutters	Item code
		Wet diamond core drill bit WCHP-25/450 (1 1/4" UNC) EXPERT EKF		25		2	wchp-sf25/450
		Wet diamond core drill bit WCHP-32/450 (1 1/4" UNC) EXPERT EKF		32		3	wchp-sf32/450
		Wet diamond core drill bit WCHP-42/450 (1 1/4" UNC) EXPERT EKF		42		4	wchp-sf42/450
		Wet diamond core drill bit WCHP-52/450 (1 1/4" UNC) EXPERT EKF		52		5	wchp-sf52/450
		Wet diamond core drill bit WCHP-62/450 (1 1/4" UNC) EXPERT EKF		62		6	wchp-sf62/450
		Wet diamond core drill bit WCHP-72/450 (1 1/4" UNC) EXPERT EKF		72		7	wchp-sf72/450
		Wet diamond core drill bit WCHP-82/450 (1 1/4" UNC) EXPERT EKF		82		8	wchp-sf82/450
₽		Wet diamond core drill bit WCHP-92/450 (1 1/4" UNC) EXPERT EKF		92		8	wchp-sf92/450
EXPERT		Wet diamond core drill bit WCHP-102/450(1 ¼" UNC) EXPERT EKF	450	102		9	wchp-sf102/450
Ш		Wet diamond core drill bit WCHP-112/450 (1 1/4" UNC) EXPERT EKF	450	112	11/4" UNC	10	wchp-sf112/450
		Wet diamond core drill bit WCHP-122/450 (1 1/4" UNC) EXPERT EKF		122		10	wchp-sf122/450
		Wet diamond core drill bit WCHP-132/450 (1 1/4" UNC) EXPERT EKF		132	_	11	wchp-sf132/450
		Wet diamond core drill bit WCHP-142/450 (1 1/4" UNC) EXPERT EKF		142		11	wchp-sf142/450
		Wet diamond core drill bit WCHP-152/450 (1 1/4" UNC) EXPERT EKF		152		12	wchp-sf152/450
		Wet diamond core drill bit WCHP-162/450 (1 1/4" UNC) EXPERT EKF		162		12	wchp-sf162/450
		Wet diamond core drill bit WCHP-172/450 (1 1/4" UNC) EXPERT EKF		172		13	wchp-sf172/450
		Wet diamond core drill bit WCHP-182/450 (1 1/4" UNC) EXPERT EKF		182		13	wchp-sf182/450
		Wet diamond core drill bit WCHP-200/450 (1 1/4" UNC) EXPERT EKF		200		15	wchp-sf200/450







DRILLING

TEMPLATES



Picture	Name	Iteam code
	Wall box template set 68 mm EXPERT EKF	sh-d68-k
	Wall box template set 72 mm EXPERT EKF	sh-d72-k
	Wall box template set 82 mm EXPERT EKF	sh-d82-k
E cor 7072	Wall box template 1 gang 68 mm EXPERT EKF	sh-d68-1
0-0	Wall box template 1 gang 72 mm EXPERT EKF	sh-d72-1
o ţ o	Wall box template 1 gang 82 mm EXPERT EKF	sh-d82-1
Dec. 072	Wall box template 2 gang 68 mm EXPERT EKF	sh-d68-2
1	Wall box template 2 gang 72 mm EXPERT EKF	sh-d72-2
	Wall box template 2 gang 82 mm EXPERT EKF	sh-d82-2
Element 072°	Wall box template 3 gang 68 mm EXPERT EKF	sh-d68-3
1- - 1	Wall box template 3 gang 72 mm EXPERT EKF	sh-d72-3
	Wall box template 3 gang 82 mm EXPERT EKF	sh-d82-3
El 972	Wall box template 4 gang 68 mm EXPERT EKF	sh-d68-4
1-	Wall box template 4 gang 72 mm EXPERT EKF	sh-d72-4
	Wall box template 4 gang 82 mm EXPERT EKF	sh-d82-4
10 mer. 0772	Wall box template 5 gang 68 mm EXPERT EKF	sh-d68-5
1	Wall box template 5 gang 72 mm EXPERT EKF	sh-d72-5
	Wall box template 5 gang 82 mm EXPERT EKF	sh-d82-5
ceesesses	Wall box template 10 gang 32 mm EXPERT EKF	sh-d32-10

	Picture	Name	Description	Outer diameter, mm	Maximum speed, rpm	Thickness / height of the cutters, mm	Depth of cut, mm	Item code
	Perce	Diamond disc Segmented (125×22,23 mm) MASTER EKF	Concrete, curbstone, fireclay brick, brick, paving slabs,	125	12200	2,2 / 10	20	dd-125s
œ	MASTER 04-120e	Diamond disc Segmented (150×22,23 mm) MASTER EKF	hard sandstone	150	10200	2,2 / 10	30	dd-150s
MASTER		Diamond disc Segmented (230×22,23 mm) MASTER EKF	concrete brick stone	230	6600	2,7 / 10	60	dd-230s
		Diamond disc Turbo (125×22,23 mm) MASTER EKF	Concrete, curbstone, brick, paving slabs,	125	12000	2,2 / 10	20	dd-125t
	HANTED ALCON	Diamond disc Turbo (150×22,23 mm) MASTER EKF	hard sandstone, granite	150	10200	2,3 / 10	30	dd-150t
		Diamond disc Turbo (230×22,23 mm) MASTER EKF	concrete brick stone	230	6600	2,8 / 10	60	dd-230t
		Diamond disc Hard Segmented (125×22,23 mm) EXPERT EKF	Concrete, curbstone, brick, paving slabs, hard sandstone, granite, reinforced concrete	125	12200	2/10	20	dd-125hps
	DEKP	Diamond disc Hard Segmented (150×22,23 mm) EXPERT EKF	reinforced concrete	150	10200	2,2 / 10	30	dd-150hps
RT	***	Diamond disc Hard Segmented (230×22,23 mm) EXPERT EKF	brick stone	230	6800	2,4 / 10	60	dd-230hps
EXPERT	DEKF	Diamond disc Turbo Segmented (125×22,23 mm) EXPERT EKF	Reinforced concrete, mesh reinforced concrete, non-reinforced concrete, curbstone, natural stone, paving slabs, brick	125	12200	2,1 / 10	20	dd-125ts
	a III	Diamond disc Turbo Segmented (230×22,23 mm) EXPERT EKF	reinforced concrete concrete brick stone	230	6600	2,5 / 10	60	dd-230ts

ekfgroup.com ekfgroup.com 73



DRILL BITS PROFESSIONAL













Picture	Name	Total length, mm	Drill depth, mm	Diameter, mm	Item code
	Concrete drill bit SDS-plus 6×110 mm 4 cutters PROFESSIONAL EKF	110	45	6	db-6-110-4x4-ue
	Concrete drill bit SDS-plus 6×160 mm 4 cutters PROFESSIONAL EKF	160	95	6	db-6-160-4x4-ue
ĮU	Concrete drill bit SDS-plus 6×210 mm 4 cutters PROFESSIONAL EKF	210	142	6	db-6-210-4x4-ue
Ш	Concrete drill bit SDS-plus 8×110 mm 4 cutters PROFESSIONAL EKF	110	45	8	db-8-110-4x4-ue
	Concrete drill bit SDS-plus 8×160 mm 4 cutters PROFESSIONAL EKF	160	95	8	db-8-160-4x4-u
8	Concrete drill bit SDS-plus 8×210 mm 4 cutters PROFESSIONAL EKF	210	142	8	db-8-210-4x4-u
0	Concrete drill bit SDS-plus 8×110 mm 4 cutters PROFESSIONAL EKF	110	45	10	db-10-110-4x4-u
8	Concrete drill bit SDS-plus 8×160 mm 4 cutters PROFESSIONAL EKF	160	95	10	db-10-160-4x4-u
0	Concrete drill bit SDS-plus 8×210 mm 4 cutters PROFESSIONAL EKF	210	142	10	db-10-210-4x4-u
83	Concrete drill bit SDS-plus 12×160 mm 4 cutters PROFESSIONAL EKF	160	93	12	db-12-160-4x4-u
	Concrete drill bit SDS-plus 12×210 mm 4 cutters PROFESSIONAL EKF	210	133	12	db-12-210-4x4-u
	Concrete drill bit SDS-plus 12×260 mm 4 cutters PROFESSIONAL EKF	260	180	12	db-12-260-4x4-ı





DRILL BITS



DRILL BITS EXPERT













	Picture	Name	Total length, mm	Drill depth, mm	Diameter, mm	Item code
	_	Concrete drill bit SDS-plus 6×110 mm 4 cutters, 4S spiral EXPERT EKF	110	45	6	db-6-110-4x4
	1	Concrete drill bit SDS-plus 6×160 mm 4 cutters, 4S spiral EXPERT EKF	160	95	6	db-6-160-4x4
	71	Concrete drill bit SDS-plus 6×210 mm 4 cutters, 4S spiral EXPERT EKF	210	142	6	db-6-210-4x4
	Ш	Concrete drill bit SDS-plus 8×110 mm 4 cutters, 4S spiral EXPERT EKF	110	45	8	db-8-110-4x4
F.	111	Concrete drill bit SDS-plus 8×160 mm 4 cutters, 4S spiral EXPERT EKF	160	95	8	db-8-160-4x4
EXPERT		Concrete drill bit SDS-plus 8×210 mm 4 cutters, 4S spiral EXPERT EKF	210	142	8	db-8-210-4x4
Ш		Concrete drill bit SDS-plus 10×160 mm 4 cutters, 4S spiral EXPERT EKF	160	95	10	db-10-160-4x4
	83	Concrete drill bit SDS-plus 10×210 mm 4 cutters, 4S spiral EXPERT EKF	210	142	10	db-10-210-4x4
	83	Concrete drill bit SDS-plus 12×160 mm 4 cutters, 4S spiral EXPERT EKF	160	93	12	db-12-160-4x4
		Concrete drill bit SDS-plus 12×210 mm 4 cutters, 4S spiral EXPERT EKF	210	133	12	db-12-210-4x4
	63	Concrete drill bit SDS-plus 14×210 mm 4 cutters, EXPERT EKF	210	132	14	db-14-210-4x4
	Altr	Concrete drill bit SDS-plus 14×260 mm 4 cutters. EXPERT EKF	260	179	14	db-14-260-4x4

DRILL BITS MASTER











	Picture	Name	Total length, mm	Drill depth, mm	Diameter, mm	Item code
	O.	Concrete drill bit SDS-plus 6×110 mm 2 cutters, 4S spiral MASTER EKF	110	45	6	db-6-110-2x4
	ĮĮ	Concrete drill bit SDS-plus 6×160 mm 2 cutters, 4S spiral MASTER EKF	160	95	6	db-6-160-2x4
~		Concrete drill bit SDS-plus 8×210 mm 2 cutters, 4S spiral MASTER EKF	210	142	6	db-6-210-2x4
MASTER	G.	Concrete drill bit SDS-plus 8×110 mm 2 cutters, 4S spiral MASTER EKF	110	45	8	db-8-110-2x4
Σ		Concrete drill bit SDS-plus 8×160 mm 2 cutters, 4S spiral MASTER EKF	160	95	8	db-8-160-2x4
	ä	Concrete drill bit SDS-plus 8×210 mm 2 cutters, 4S spiral MASTER EKF	210	142	8	db-8-210-2x4
		Concrete drill bit SDS-plus 10×160 mm 2 cutters, 4S spiral MASTER EKF	160	95	10	db-10-160-2x4
		Concrete drill bit SDS-plus 10×210 mm 2 cutters, 4S spiral MASTER EKF	210	142	10	db-10-210-2x4






74 ekfgroup.com ekfgroup.com 75



	Picture	Name	Diameter, mm	Shank type	Total length, mm	Step height, mm	Item code
		Step drill bit ST-4-12/1 HSS	4, 5, 6, 7, 8, 9, 10, 11, 12	1/4"	70		ST-4-12/1
MASTER	TO POST DE CONT	Step drill bit ST-4-20/2 HSS	4, 6, 8, 10, 12, 14, 16, 18, 20	Three-point	75	5	ST-4-20/2
Σ		Step drill bit ST-4-30/2 HSS	4, 6, 8, 10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30	Three-point	100	3	ST-4-30/2
		Step drill bit ST-4-39/3 HSS	4, 6, 9, 12, 15, 18, 21, 24, 27, 30, 33, 36, 39	Three-point	113		ST-4-39/3














PERSONAL PROTECTIVE EQUIPMENT



	Picture	Name	PVC DOT
MASTER		Description	Knitted cotton gloves made of blended yarn. Seamless knit technology makes them very comfortable to wear. PVC dot pattern provides high abrasion resistance and excellent palm protection
MAS		Features	Knit grade: 10 Base composition: 60% cotton, 40% polyester Coating composition: 100% PVC Coating coverage: ½ (palm and fingertips) PVC coating type: dot pattern Two sizes (9, 10)
		Item code	pe10ct-9-mas, pe10ct-10-mas
	Picture	Name	PROTECTION safety work gloves with a single layer latex coating
MASTER		Description	Universal cotton safety gloves with a single layer natural latex coating. The latex coating prevents the ingress of moisture and dirt and ensures high abrasion resistance
MAS ⁻		Features	 Knit grade: 13 Base composition: 60% cotton, 40% polyester Coating composition: 100% PVC Coating coverage: ½ [palm and fingertips] Coating type: wrinkled, single coated Two sizes [9, 10]

	Picture	Name	PROFI wrinkled latex coated work gloves
ERT		Description	All-purpose polyester-based wrinkled latex palm gloves with nylon liner. Wrinkled latex palm coating enables excellent grip on slippery surfaces. Great choice for working with glass, sharp or cutting materials
EXPERT		Features	Note: Note: 15 Rase composition: 100% polyester Coating composition: 100% natural latex Coating coverage: ½ [palm and fingertips] Coating type: wrinkled, single coated Two sizes [9, 10]
		Item code	pet5nl-proxima, pet5nl-t0-proxima

Item code





pe13lt-9-mas, pe13lt-10-mas



PERSONAL PROTECTIVE EQUIPMENT


	Picture	Name	PROFI Touch for finishing work
RT		Description	Intended for delicate finishing work like wallpaper hanging, painting, furniture assembly, and other decoration jobs, these fine lint-free gloves offer excellent sensitivity and do not mar finished surfaces
EXPERT		Features	 Knit grade: 15 Base composition: 95% polyamide + 5% spandex Coating composition: 100% water-based polyurethane Three sizes [7, 8, 9]
		Item code	pe15pm-7-exp, pe15pm-8-exp, pe15pm-9-exp

	Picture	Name	WINTER PVC DOT thermal work gloves
IONAL		Description	All-purpose gloves for low-temperature applications. The gloves are fleece-lined, keeping you warm and providing maximum comfort. PVC dots provide excellent sensitivity and grip. Designed for moderate mechanical load
PROFESSIONAL	Ment *	Features	Knit grade: 7 Base composition: 100% acrylic wool Coating composition: 100% PVC Coating coverage: ½ [palm and fingertips] Coating type: dot pattern Two sizes (9, 10)
		Item code	pe7ac-9-pro, pe7ac-10-pro

	Picture	Name	PROFI WINTER wrinkled latex coated thermal work gloves
SSIONAL		Description	All-purpose gloves for low-temperature applications. The gloves are fleece-lined inside, keeping you warm and providing maximum comfort. Wrinkled latex palm coating enables secure grip on slippery surfaces. Great choice for working with glass, sharp or cutting materials. Improved thumb protection with full latex coating. Designed for high mechanical loads
PROFESSI	Mark.	Features	Knit grade: 10 Base composition: 100% acrylic wool Coating composition: 100% natural latex Coating type: wrinkled, single coated Coating coverage: ½ [palm and fingertips] Base colour: safety orange, safety green Coating colours: blue, black
		Item code	pe10lt-9-pro, pe10lt-10-pro










TOOL BAGS, BACKPACKS, BELTS

TOOL BAGS, BACKPACKS, BELTS



Picture	Name	Universal electrician tool bag C-01 PROFESSIONAL EKF
	Dimensions	450×330×380 mm
	Description	Universal electrician tool bag C-01 is designed for tool storage and carrying
	Features	• 100% durable 1680D Oxford polyester • Universal strap with soft anti-slip shoulder pad • Extra stitching in load-bearing areas. Increased tool capacity • Reinforced zipper with durable links • External pockets for safe carry of multimeter and digital clamp meter • Roomy and well thought-out interior for every type of tool • Rigid oil- and water-resistant bottom
	Item code	C-01

	Picture	Name	Tool organizer C-10 PROFESSIONAL EKF
	E extr	Dimensions	310×60×420 mm
4		Description	Tool Organizer C-10 is a convenient backpack insert that can be used to store frequently accessed tools
PROFESSIONAL		Features	Improves the capacity of the tool bag or backpack Neatly organizes most frequently used tools, keeping them within hand's reach 100% durable 1680D Oxford polyester Pockets for screwdrivers and pliers. All the essentials at the fingertips Additional stitching in the load-bearing areas At 31×42 cm the organizer is compatible with C-07 and C-08 backpacks, as well as C-01 tool bag and C-02 messenger bag
		Item code	C-10





Picture	Name	Service engineer's messenger bag C-02 PROFESSIONAL EKF
	Dimensions	400×170×300 mm
0	Description	Service engineer's messenger bag is designed to carry and store tools, documents, as well as a laptop
 ERRE	Features	 Dedicated compartment for a laptop, electronics, or a change of clothes Reinforced zipper with durable links Reinforced stitching in load-bearing areas Universal strap with soft anti-slip shoulder pad Spacious interior with tool pockets Large outer pocket with a flap for documents
	Item code	C-02
Picture	Name	Belt tool bag with shoulder strap and cover flap C-14 PROFESSIONAL EKF
	Dimensions	250×150×300 mm
	Description	Tool bag C-14 is designed for electrical installation and routine maintenance work
EHF	Features	Hard-wearing EVA pouches. Hold their shape well. Perfect for tools and hardward Deep pockets, positioned at different levels, improve the user's mobility Universal strap with soft anti-slip shoulder pad The strap can also be used as a belt, extending the capabilities of the bag Well thought interior layout - all the tools are at your fingertips Cover to prevent the tools from falling out Can be carried on a toolbelt or used as an accessory for C-15 and C-12

	Item code	C-14	
Picture	Name	Tool bag with foldable stool C-06 PROFESSIONAL EKF	
	Dimensions	360×340×400 mm	
	Description	Tool bag with foldable stool C-06 is used for storing and carrying tools and as a convenient place to sit during installation of wiring accessories	
	Features	100% durable 1680D Oxford polyester Reinforced steel frame for improved safety The tool bag can be detached and used independently Universal strap with soft anti-slip shoulder pad Ideal for installing sockets and parapet channels	
	Item code	C-06	

Carry handle





82 83 ekfgroup.com ekfgroup.com






TOOL BAGS, BACKPACKS, BELTS



Picture	Name	Service engineer's backpack with retroreflective strips C-08 PROFESSIONAL EKF
	Dimensions	280×120×410 mm
DEMP	Description	Service engineer's backpack with retroreflective strips C-08 is designed to carry and store tools documents, laptop
PROFESSION	Features	Dedicated compartment for a laptop, electronics, or a change of clothes Reinforced zipper with durable links Reinforced stitching in load-bearing areas Padded back and shoulder straps for greater comfort Spacious interior with tool pockets Large outer pocket for documents and papers
	Item code	C-08

Picture	Name	Heavy-duty tool backpack C-07 PROFESSIONAL EKF
	Dimensions	400×150×450 mm
	Description	Heavy-duty tool backpack C-07 is designed to store and carry tools
□ CICE	Features	• 100% durable 1680D Oxford polyester • Padded back and shoulder straps for greater comfort • Rubberized bottom to protect contents from oil and moisture • Two carrying handles for improved hand carry comfort • Retroreflective strips for improved safety • Special pocket for the multimeter • Reinforced zipper with durable links • Extra stitching in load-bearing areas • Roomy interior with internal pockets for secure tool carry • Reinforced carrying handles, capable of supporting heavy tool weight with fabric wraparound to reduce hand pressure (up to 20 kg)
	Item code	C-07





	Picture	Name	Three-pouch tool belt C-12 PROFESSIONAL EKF
		Dimensions	1300 mm
		Description	Three-pouch tool belt C-12 is a convenient solution for general construction and electrical work
PROFESSIONAL		Features	Durable wide belt with Velcro fastening and padding to reduce pressure on the lumbar area Hard-wearing EVA pouches. Hold their shape well. Perfect for tools and hardware Hammer hanger, tape measure hanger Reinforced metal suspender loops Pouch pockets positioned at different levels for ease of use Durable reinforced double grommet belt Deep pouches to securely hold the tools Additional stitching in the load-bearing areas
		Item code	C-12

	Picture	Name	Tool belt with harness and 3 pouches C-15 PROFESSIONAL EKF
PROFESSIONAL		Dimensions	1300 mm
		Description	Three-pouch tool belt with harness C-15 is an excellent solution for general construction and electrical work
		Features	• 100% durable 1680D Oxford polyester • Hard-wearing EVA pouches. Hold their shape well. Perfect for tools and hardware • Three-point harness for better weight distribution and reduced fatigue • Bit driver holster with dedicated core bit holder • Wide belt with Velcro fastening and padded inserts to reduce pressure on the lumbar area • Durable reinforced double grommet belt • Pouches and harness compatible with C-12 tool belt bag • Additional stitching in the load-bearing area
		Item code	C-15







TOOL BAGS, BACKPACKS, BELTS

	Picture	Name	Safety vest with reflective strips S-22 PROFESSIONAL EKF
PROFESSIONAL		Description	Adjustable safety vest with reflective strips and tool pockets S-22 is a convenient solution for tool carry during general construction and electrical work
		Features	• 100% durable 1680D Oxford polyester • Hard-wearing EVA pouches. Hold their shape well. Perfect for tools and hardware • The back of the vest is made of denim-like durable natural cotton material. It's much easier to work in this vest, especially in hot weather • Deep pockets and pouches positioned at different levels, improve the user's mobility • Integrated vest carry and safety loop • Customizable at waist and shoulders. Can be worn over warm clothing • Additional stitching in the load-bearing areas • Reflective strip for improved safety • Tape measure hanger. Insulation tape hanger. Wire bundle hanger • Transparent badge pocket
		Item code	C-22









Open to cooperation and looking for distributors

All countries across the Middle East & Africa

E-mail:

sales@ekfgroup.com

Social media:





EKFGROUP.COM